OLYMPUS®

Stylus Verve™

Designed to Do More.™

Color so bold it unleashes your creativity. The energy in these six bright designs will capture any moment with enthusiasm.

Power so real, it features a 4.0 megapixel CCD, TruePic TURBO™ Image Processor and 16 shooting options – from perfect portraits to QuickTime® movies with audio.

Style so perfect, it makes a bold statement wherever you go.

Color. Power. Style. Find Your Verve.

available in six stylish colors

olympusamerica.com/stylus-verve

OLYMPUS FASHIONWEEK When the world's top designers meet, we're proud to be one of them. The new Stylus Verve™. Official Camera of Olympus Fashion Week.

Style & Design Fashionably designed and loaded with innovative features, the colorful, all-weather Stylus Verve™ puts the focus on you in any setting.

All-Weather Construction Engineered with a weather-resistant body so you can capture incredibly clear and colorful pictures under almost any condition.

High Resolution, Sophisticated Zoom 4.0 megapixel CCD (effective) plus 2x optical zoom, 8x total zoom capability creates sharp, vibrant images every time.

See and Feel the Difference Our exclusive TruePic TURBO™ Image Processor provides clearer, smoother, more color-accurate images. Faster processing speed means improved start-up time and less shutter delay.

16 Selectable Shooting Modes Use the easily accessible shooting mode to switch between Portrait, Self-Portrait, Landscape, Beach & Snow, Indoors, Cuisine, Night Scene and more. Also includes QuickTime® Movie Mode with audio. Recording time limited to the size of the xD Picture Card™.

Direct Print Capability Connect to any PictBridge enabled printer (such as the Olympus P-10) via the built-in USB interface. No computer required.

xD Picture Card™ Compatible Use this ultra-compact memory card to record, store and transfer your images. Available in capacities of up to 1GB.

Power Up You can be sure your Stylus Verve™ will be powered up and ready to shoot when you are with the included Lithium Ion rechargeable battery and charger.

Easy to See The 1.8" HyperCrystal LCD display makes it easy to see crisp, clear images – even in bright sunlight. And with its 160-degree tilt, you can always get the proper perspective.

The Stylus Verve™ shows you a colorful new way to look at life with its highly developed capabilities and incredibly compact, stylish, all-weather design.

PictBridge | xD-Picture Card™ | Exif Print | PRINT Image Matching

Megapixel	Optical Zoom	Total Zoom	All-Weather	Auto-Connect		
4.0 Effective	2x	8x Optical & Digital	Construction	USB	QuickTime	Li-Ion

OLYMPUS®

Stylus Verve™

Designed to Do More.™

STYLUS VERVE™ Specifications

Stock No. 275540 (Silver), 227535 (White), 225530 (Black), 225550 (Blue), 225555 (Red), 225545 (Copper)

CCD Imager	4.0 megapixel (effective) 4.2 megapixel gross 1/2.5 type (o.4 type) CCD
Lens	5.8-11.6mm (35-70mm equivalent in 35mm photography), 5 lens in 3 groups
Digital Zoom	Seamless to 8x (2x optical and 4x digital combined)
Aperture Range	f3.5 – f5.9
Shutter Speeds	AUTO 1/2-1/1000 (Night Scene - longest 4 sec.)
ISO	64/100/200/400/Auto (64 – 250) (Scene of "Indoor" and "Candle" only: Auto up to 500)
Recording Modes	Still Image: DCF Standard (JPEG, EXIF 2.2). DPOF, PIM 2.5 compatible Movie mode: DCF Standard (QuickTime motion JPEG)
Adjustable Resolutions	2,272 x 1,704 JPEG (SHQ, HQ) 2,048 x 1,536 JPEG (SQ1) 1,600 x 1,200 JPEG (SQ2) 1,280 x 960 JPEG (SQ2) 1,024 x 768 JPEG (SQ) 640 x 480 JPEG (SQ)
QuickTime® Movie	15 frames per second in 320 X 240 HQ mode 15 frames per second in 160 X 120 SQ mode; Movies are only limited in length by the size of the xD Picture Card™
Image Adjustment Modes	2-in-1 picture mode
TruePic TURBO™	Significantly improved image quality, faster processing speed, noise reduction, uses all pixels at all resolutions, pixel micro-smoothing
Noise Reduction	Mode available at shutter speeds of 0.5 second or longer
Pixel Mapping	Automatic Pixel Mapping (APM) available via menu setting
DPOF **(Digital Print Order Format)**	Print reserve (single, all, number of copies), Date
Panorama	Up to 10 frames automatically stitchable with Olympus Master software when using an Olympus brand xD Picture Card™
Sequence	1.3 frames per second in HQ mode
LCD	1.8" Enhanced HyperCrystal LCD (134K Pixel TFT) for taking and viewing pictures (no optical viewfinder)
Focusing System	Autofocus (Contrast detection)
Focusing Ranges	Normal mode: 20in. (0.5m) – infinity Macro mode: 8in. (0.2m) – infinity Super Macro mode: 3.5in. – 8in. (0.08m – 0.5m) (Tele side only, flash off)
Exposure Compensation	±2Ev (step 1/3 Ev)
Scene Programming	Portrait, Indoor, Beach & Snow, Portrait+ Landscape, Night Scene, Self-Portrait, Cuisine, Two-in-One, Panorama, Landscape, Self-Portrait+Self-Timer, Behind Glass, Candle, Sunset, Fireworks
Metering System	Digital ESP multi-pattern, Spot
White Balance System	iESP multi-pattern auto TTL, pre-set manual (Daylight, Overcast, Tungsten and Fluorescent)
Flash	Built-in
Flash Modes	Auto for low and backlight Red-eye Reduction Fill-in Off
Flash Working Range	Wide: 8in. – 9.2ft. (0.2m – 2.8m), Tele: 8in. – 6ft. (0.2m – 2.0m)
Flash Recharging Time	5 seconds
Removable Media	xD Picture Card™, 16 MB included
Selftimer	12 seconds
Settings Memorization	On/Off (Hold changes/Reset to default settings)
Outer Connectors	USB & Audio/Video multi-terminal
Auto-connect USB 2.0	mini B
System Requirements	Windows 98 rev2/ME/2000 Pro/XP and Mac OS X and higher
Image Playback:	Still image: Index display, up to 4x enlargement, slide show, scene rotation
Movie Playback:	Normal, Frame by Frame
Operating Environment	Operation: 32 – 104˚F (0 – 40˚C) 30 – 90% humidity Storage: -4 – 140˚F (-20 – 60˚C) 30 – 90% humidity
Power Supply	1 Li-30B Li-Ion Rechargeable Battery (included) 1 Li-30C Battery Charger (included)
Date/Time Calendar	Simultaneous recording into image data, Automatic up to 2099
Size	3.74in. (95mm) x 2.18in. (55.5mm) x 1.08in. (27.5mm) (excluding protrusions)
Weight	3.7oz. (115g) (without battery and media card)

Available Accessories

Product Number	UPC 050332-	Accessory
200893	297883	Extended 2 yr Warranty
200482	148734	Li-30B Li-Ion Rechargeable Battery
200483	148765	Li-30C Battery Charger
200488	150799	BPC-01 Power Coupler
200496	298538	Metal Neck Strap
200499	298845	Verve AC Adapter Kit (includes BP-C01 Power Coupler and D-7AC Power Cord)
200891	144422	MAUSB-100 Mobile xD Picture Card Reader/Writer
200830	139138	MAUSB-10 xD Picture Card/SmartMedia USB Reader/Writer
200837	139512	MACF-10 xD Picture Card/ Compact Flash Adapter
200835	139145	MAPC-10 xD picture Card/SmartMedia PCMCIA/PC Card Adapter
200845	296473	xD Picture Card Media Wallet
200840	139084	xD Picture Card 16MB
200841	139091	xD Picture Card 32MB
200842	139107	xD Picture Card 64MB
200843	139114	xD Picture Card 128MB
200844	139565	xD Picture Card 256MB
200859	142558	xD Picture Card 512MB

Memory Card Storage Capacity

	Quality	Pixel Resolution	16MB xD Picture Card™ (Included)	512MB xD Picture Card™
Still Image (without sound) Unit: shots	SHQ	2272 x 1704	5 shots	180 shots
	HQ	2272 x 1704	16 shots	523 shots
	SQ1	2048 x 1536	20 shots	652 shots
	SQ2	1600 x 1200	24 shots	779 shots
		1280 x 960	38 shots	1229 shots
		1024 x 768	58 shots	1879 shots
		640 x 480	90 shots	2904 shots
Still Image (with sound)	SHQ	2272 x 1704	5 shots	178 shots
	HQ	2272 x 1704	15 shots	507 shots
	SQ1	2048 x 1536	19 shots	626 shots
	SQ2	1600 x 1200	23 shots	743 shots
		1280 x 960	35 shots	1141 shots
		1024 x 768	52 shots	1681 shots
		640 x 480	76 shots	2458 shots
Movie (with sound) Unit: minutes	HQ	320 x 240	approx. 41 sec.	approx. 1300 sec.
	SQ	160 x 120	approx. 150 sec.	approx. 4800 sec.

All capacity figures are approximate.

Package Contents

- Stylus Verve™ Digital Camera
- 16MB xD Picture Card™
- Wrist Strap
- Camera WIN/Mac USB Cable
  Audio/Video cable
- Li-30B Li-Ion Rechargeable Battery
  Li-30C Battery Charger
- Quick Start Guide
  Basic Instruction Manual
  Warranty Card
- CD ROM: Olympus Master Software and Camera reference manual

OLYMPUS SCHOOL OF DIGITAL PHOTOGRAPHY

The Olympus School of Digital Photography is a one-day workshop covering everything from digital image capture to final output. To register, visit www.olympusphotoschool.com or call 1-800-645-8100 x6161.

Specifications subject to change without notice or obligation on the part of the manufacturer. ©2004 Olympus Imaging America Inc. All rights reserved. Printed in the United States of America. Olympus and Stylus® are trademarks or registered trademarks of Olympus Corporation, Olympus Imaging America Inc. or their affiliated entities. All other trademarks and registered trademarks listed herein are the property of their respective holders.
D1198-0904